




Republic of the Philippines
MURCIA WATER DISTRICT
 Municipality of Murcia
 Province of Negros Occidental
 Email add: murciawaterdistrict@gmail.com
 Tel/Fax No. (034) 458-8844

REQUEST FOR QUOTATION

P.R. No.: EOM-2024-01-003
ABC: 225,500.00

Name of Supplier: _____
Address: _____

Please quote your bid price on the items / listed below, subject to the General Condition on the last page, stating the shortest time of delivery and submit your quotation duly signed by your representative in the returned envelope attached herewith.


CHARMAINE V. FLORES
 BAC Secretariat

Note: 1) All entries must be legible.
 2) Service / Delivery Period within the number of days agreed upon between the supplier and the Procuring Entity.
 3) Warranty shall be for a period of _____ from date of acceptance by the procuring entity.
 4) Price validity shall be a period of at least _____ calendar days.
 5) PhilGEPs Registration Certificate shall be attached upon submission of the Quotation, if applicable.
 6) Bidders shall submit Original Brochures showing certification of the product being offered (optional).
 7) Mode of Delivery: [] Pick-up (Schedule) [/] Freight on Board (FOB)
 8) Place of Delivery: **MURCIA WATER DISTRICT ADMIN BUILDING**
 9) Delivery Period: **within 15 days upon issuance of NOA**
 10) Terms of Payment: **within 30 days upon delivery**
 11) All items are subject to 6% VAT.

Item No.	Unit	Item and Description	Quantity	Unit Price	Total Amount
1	unit	3"Ø PSRV (F/F) 3"Ø Pressure Sustaining & Reducing Valve (F/F) Pilot System Specifications Standard Materials: Pilots: Body:Stainless steel Elastomers: Synthetic Rubber Springs: Galvanized Steel or Stainless Steel Tubing & Fittings: Stainless Steel 316 or Copper and Brass Accessories: Stainless Steel 316, Brass and Synthetic Rubber Elastomers Technical Data Specifications; End Connections(Pressure Ratings): Flanged: ISO PN16, PN25 (ANSI Class 150, 300) Threaded: BSP or NPT Valve Patterns: "Y" pattern Standard Materials; Body & Actuator: Ductile Iron Internals: Stainless Steel, Bronze & Coated Steel Diaphragm: Synthetic Rubber Nylon fabric-reinforced Seals: Synthetice Rubber	1		

Item No.	Unit	Item and Description	Quantity	Unit Price	Total Amount
2	piece	Coating: Fusion Bonded Epoxy, RAL 5005 (Blue) approved for drinking water or Electrostatic Polyester Powder 3"Ø Gate Valve D.I. (F/F) Non-rising stem, Square nut gate valve, Ductile iron body, Ansi 150, Flange type, w/o accessories	1		
3	set	1"Ø AIR RELEASE VALVE Plastic Body, Threaded Type Maximum Working Pressure: 16 Bar Maximum Working Temperature: 60 C Discharge High Air flow rates up to 160 m ³ /h Size: 1" Ø	2		
4	piece	4"Ø Gate Valve (F/F) Non-rising stem, Square nut gate valve, Ductile iron body, Ansi 150, Flange type, w/o accessories	1		
5	piece	5"Ø Gate Valve (F/F) Non-rising stem, Square nut gate valve, Ductile iron body, Ansi 150, Flange type, w/o accessories ***** Nothing Follows *****	1		
Grand Total					

Amount in Words: _____

After having carefully read and accepted your General Condition. I / We quote you on the item at prices noted above.

Printed Name / Signature

Tel. No. / Fax No.

TIN No.

Date

Canvasser/Procurement Unit:  Lady Lee M. Alintana